CONFORMITY DETERMINATION

for the 2035 Regional Transportation Plan and the 2008-2011 Transportation Improvement Program for the Houston-Galveston Transportation Management Area

Graciela Lubertino 9/10/2009

HOUSTON-GALVESTON AREA COUNCIL TRANSPORTATION DEPARTMENT

Board Resolution





CERTIFYING THAT THE 2035 REGIONAL TRANSPORTATION PLAN AND THE 2008-2011 TRANSPORTATION IMPROVEMENT PROGRAM ARE IN CONFORMITY WITH THE CLEAN AIR ACT OF 1990, AS AMENDED, AND THE SAFE, ACCOUNTABLE, FLEXIBLE AND EFFICIENT TRANSPORTATION EQUITY ACT – A LEGACY FOR USERS OF 2005.

WHEREAS, it has become necessary to certify that the 2035 Regional Transportation Plan and the 2008-2011 Transportation Improvement Program were found to be in conformity for VOC and NOx motor vehicle emissions budgets contained in *Revisions to the State Implementation Plan for the Control of Ozone Air Pollution, Houston/Galveston/Brazoria Ozone Nonattainment Area*; and

WHEREAS, the 2035 Regional Transportation Plan (RTP) and the 2008-2011 Transportation Improvement Program (TIP) have met the requirements set forth in the Conformity State Implementation Plan issued jointly by the U.S. Department of Transportation and the Environmental Protection Agency (EPA); and

WHEREAS, vehicle emissions estimates resulting from the implementation of the transportation facility and service improvements recommended in the 2035 Regional Transportation Plan and the 2008-2011 Transportation Improvement Program provide for expeditious implementation of transportation control measures in its applicable implementation plan; and

WHEREAS, the 2035 Regional Transportation Plan and the 2008-2011 Transportation Improvement Program contribute to annual emissions reductions consistent with Sections 182 (b)(1) and 187 (a)(7) of the Clean Air Act, as amended; and

WHEREAS, implementation of the transportation facilities and services recommended in the 2035 Regional Transportation Plan Update and the 2008-2011 Transportation Improvement Program would result in lower total vehicle emissions than the 1990 base year emissions and the motor vehicles emissions budget (MVEB); and

NOW THEREFORE, be it resolved by the Transportation Policy Council for the Houston-Galveston Transportation Management Area that the 2035 Regional Transportation Plan and the 2008-2011 Transportation Improvement Program are in conformity with the 1990 U.S. Clean Air Act as amended, and the Safe Accountable Flexible and Efficient Transportation Equity Act – A Legacy for Users of 2005.

PASSED AND APPROVED this 28th day of August 2009 at a regularly scheduled meeting of the Transportation Policy Council for the Houston-Galveston Transportation Management Area.

APPROVED:

ATTEST:

James Patterson, Chairman

Transportation Policy Council

Tom Reid, Secretary

Transportation Policy Council

Table of Contents

	solution	
Table of	Contents	3
List of Fi	gures	4
List of Ta	ibles	4
List of A	ppendices	5
List of A	bbreviations	5
Executive	e Summary	10
Milesto	ones	10
Confo	mity Requirements	11
Region	al Inventory	12
Motor	Vehicle Emission Budgets	12
Confor	mity Tests	12
Model	ing	13
Confor	mity Analysis Results	13
Backgi	round Information on Conformity	14
1.0 In	troductiontroduction	15
1.1	MPO Organization and Role	15
1.2	Purpose	16
1.3	Conformity Criteria	16
1.4	Document Format	17
1.5	Electronic Data Submittal	17
1.6	Checklist	17
2.0 20	035 RTP & 2008-2011 TIP Conformity to the SIP	19
2.1	Overview	19
2.2	Submittal Frequency	19
2.3	Reasonable Available Control Measures	19
2.4	Regionally Significant Projects	20
2.5	Regionally Significant Travel Projects/Programs	
2.5.1	System Capacity	21
2.5.2	2 Demand Management	21
2.5.3	3 Operations Management	22
2.5.4	Livable Centers: Connecting transportation and land use	22
2.6	Locally Funded Projects/Programs	22
2.7	Exempt Projects/Programs	23
2.8	Constraints	23
2.8.	Long-Range Financial Constraint (RTP)	23
2.8.2	Short-Range Financial Constraint (TIP)	24
2.8.3	Air Quality/Motor Vehicle Emissions Budgets	24
3.0 M	lodeled Activity	25
3.1	Land-Use Model	25
3.2	Travel Demand Model	26
3.2.	Model Description	26
3.2.2	2 Model Validation	27
3.2.3	Network Development	27

3	3.2.5 Transit Systems	28
3	3.2.6 Roadway VMT	28
4.0	Emission Factors/MOBILE Model	35
4.1	Overview	35
4.2	MOBILE Input Parameters	36
4.3	Emission Factor Adjustments	36
5.0	Mobile Source Emission Reduction Strategies	37
5.1	TCMs	37
5	5.1.1 Timely Implementation of TCMs	37
5	5.1.2 Project "Slippage"	37
5.2	VMEPs	37
5.3	CMAQ	38
5.4	TERP38Error! Bookmarl	k not defined.
5.5	Summary	38
6.0	Determination of Regional Transportation Emissions	39
6.1	Procedure	39
6.2	Calculated Link-Based Emissions	41
6.3	Post-Process Adjustments	41
6.4	Final Emission Analysis Results	42
7.0	Interagency Consultation	43
8.0	Public Participation	44
	of Figures	12
_	e 1: VOC Emissions Summary	
_	2: NOx Emission Summary	
Figure	e 3: TTI Suite	40
List	of Tables	
	1: Mid-Course Review Motor Vehicle Emission Budgets	
Table	2: Conformity Analysis Summary	13
	3: Comparison of Forecast Data for Conformity Years	
	4: Base Year (2002) Internal Trips by Purpose for the Eight-County Transing Region	
Table	5: 2002 Network for the Eight-County Transportation Planning Region	on 30
Table	6: Internal Trips by Purpose for the Eight-County Transportation Planfor 2007, 2009, 2019, 2025 and 2035	nning Region
Table	7: Roadway Networks for the Eight-County Transportation Planning 2007, 2009, 2019, 2025 and 2035	Region for
Table	8: Vehicle Miles Traveled for the Eight-County Transportation Plann for 2007, 2009, 2019, 2025 and 2035	ing Region
	9: Non-Adjusted Link-Based Emissions	

List of A	ppendices
2 Applica 3 Travel 4 VMEH 5 Post P 6 TTI St 7 Final I 8 MOBI 10 MOBI 11 Final I 12 Project 13 TCM 14 Approd 15 Interage	rocess uite of Programs RTP Link Listing ILE Input Parameters ILE Information and Fact Sheets ILE Input and Output Files MOBILE Emissions Factors It Listing Timely Implementation oval/Adequacy Findings of MVEBs gency Conformity Consultation Committee
List of Al	bbreviations
AERCO: ALVW: AQI: AQM: BA: BACT: BAP: BAQC: BART: BCCA: BER: BPA: CAAA: CAAA:	Area Emission Reduction Credit Organization Adjusted Loaded Vehicle Weight Air Quality Index Air Quality Model Baseline Activity Best Available Control Technology Bureau of Air Policy Bureau of Air Quality Control Best Available Retrofit Technology Business Coalition for Clean Air Baseline Emission Rate Beaumont/Port Arthur Ozone Nonattainment Area Clean Air Act of 1990 Clean Air Act Amendments of 1990 Clean Air Responsibility Enterprise
CARE: CEM: CMAQ: CMSA:	Continuous Emission Monitor Congestion Mitigation/Air Quality funds under ISTEA and TEA21 Consolidated Metropolitan Statistical Area (the Houston-Galveston-

 Brazoria CMSA consists of the Houston PMSA [Chambers, Fort Bend, Harris, Liberty, Montgomery and Waller Counties], the Galveston-Texas City PMSA [Galveston County], and the Brazoria PMSA [Brazoria

County].

CNG: Compressed Natural Gas

CO: Carbon Monoxide CO2: Carbon Dioxide

COAST: Coastal Oxidant Assessment for Southeast Texas

COG: Council of Governments

COPD: Chronic Obstructive Pulmonary Disease
DERC: Discrete Emission Reduction Credit

DFW: Dallas/Fort Worth Ozone Nonattainment Area

EBTA: Emissions Banking and Trading of Allowances (SB7)

EBTP: Emissions Banking and Trading Program

EGF: Electric Generating Facility

EPA: Environmental Protection Agency

EPN: Emission Point Number
ERC: Emission Reduction Credit
ERP: Emission Reduction Plan

ESAD: Emission Specifications for Attainment Demonstration

ESL: Effects Screening Level
ETR: Employer Trip Reduction
FCAA: Federal Clean Air Act
FCFF: Federal Clean Fuel Fleet
FIN: Facility Identification Number
FTA: Federal Transit Administration

GHP: Federal Transit Administration GHP: Greater Houston Partnership

GHRCP: Greater Houston Regional Clean Cities Program

GIS: Geographic Information Systems
GVWR: Gross Vehicle Weight Rating
HAP: Hazardous Air Pollutant

HC: Hydrocarbons

HCOEM: Harris County Office of Emergency Management

HDDV3: Heavy-Duty Diesel Vehicles Class 2b (8,501-10,000 lbs. GVWR)
HDDV4: Heavy-Duty Diesel Vehicles Class 3 (10,001-14,000 lbs. GVWR)
HDDV5: Heavy-Duty Diesel Vehicles Class 4 (14,001-16,000 lbs. GVWR)
HDDV6: Heavy-Duty Diesel Vehicles Class 5 (16,001-19,500 lbs. GVWR)
HDDV7: Heavy-Duty Diesel Vehicles Class 6 (19,501-26,000 lbs. GVWR)
HDDV7: Heavy-Duty Diesel Vehicles Class 7 (26,001-33,000 lbs. GVWR)
HDDV8a: Heavy-Duty Diesel Vehicles Class 8a (33,001-60,000 lbs. GVWR)

HDDV8b: Heavy-Duty Diesel Vehicles Class 8b (>60,000 lbs. GVWR)

HDDBS: Heavy-Duty Diesel School Buses

HDDBT: Heavy-Duty Diesel Transit and Urban Buses

HDGB: Heavy-Duty Gasoline Buses (school, transit and urban)

HDGV2b: Heavy-Duty Gasoline Vehicles Class 2b (8,501-10,000 lbs. GVWR) **HDGV3:** Heavy-Duty Gasoline Vehicles Class 3 (10,001-14,000 lbs. GVWR)

HDGV4: Heavy-Duty Gasoline Vehicles Class 4 (14,001-16,000 lbs. GVWR)
HDGV5: Heavy-Duty Gasoline Vehicles Class 5 (16,001-19,500 lbs. GVWR)
HDGV7: Heavy-Duty Gasoline Vehicles Class 6 (19,501-26,000 lbs. GVWR)
HDGV8a: Heavy-Duty Gasoline Vehicles Class 7 (26,001-33,000 lbs. GVWR)
HDGV8b: Heavy-Duty Gasoline Vehicles Class 8a (33,001-60,000 lbs. GVWR)
Heavy-Duty Gasoline Vehicles Class 8b (>60,000 lbs. GVWR)

HGA: Houston/Galveston Ozone Nonattainment Area

H-GAC: Houston-Galveston Area Council **HIRI**: Heat Island Reduction Initiative

HOV: High-Occupancy Vehicle

HRM: Houston Regional Monitoring Corporation

ILEV: Inherently Low Emission Vehicle

I/M: Inspection/Maintenance program (vehicle emissions control)

ISTEA: Intermodal Surface Transportation Efficiency Act of 1991

LAER: Lowest Achievable Emission Rate

LDDV: Light-Duty Diesel Vehicles (passenger cars)

LDDT12: Light-Duty Diesel Trucks 1 and 2 (0-6,000 lbs. GVWR) **LDDT34:** Light-Duty Diesel Trucks 3 and 4 (6,001-8,500 lbs. GVWR)

LDGV: Light-Duty Gasoline Vehicles (passenger cars)

LDGT1: Light-Duty Gasoline Trucks 1 (0-6,000 lbs. GVWR, 0-3,750 lbs. LVW)

LDGT2: Light-Duty Gasoline Trucks 2 (0-6,000 lbs. GVWR, 3,751-5,750

lbs.LVW)

LDGT3: Light-Duty Gasoline Trucks 3 (6,001-8,500 lbs. GVWR, 0-5,750 lbs.

ALVW)

LDGT4: Light-Duty Gasoline Trucks 4 (6,001-8,500 lbs. GVWR, 5,751 lbs. and

greater ALVW)

LEV: Low Emission Vehicle
LNG: Liquefied Natural Gas
LOA: Level of Activity

LPG: Liquefied Propane Gas LVW: Loaded Vehicle Weight

MACT: Maximum Achievable Control Technology MAERT: Maximum Allowable Emission Rate Table

MC: Motorcycles (gasoline)

MDERC: Mobile Discrete Emission Reduction Credit

MECT: Mass Emission Cap and Trade
MERC: Mobile Emission Reduction Credit

METRO: Metropolitan Transit Authority of Harris County

MOA: Memorandum of Agreement

MPO: Metropolitan Planning Organization

MTBE: Methyl Tertiary Butyl Ether

MTP: Metropolitan Transportation Plan MVEB: Motor Vehicle Emissions Budget

µg: Micrograms or 10⁻⁶ grams

NAAQS: National Ambient Air Quality Standards

NAMS: National Air Monitoring Stations

NESHAPs: National Emission Standards for Hazardous Air Pollutants

NLEV: National Low Emission Vehicle

NO2: Nitrogen Dioxide NOx: Nitrogen Oxides

NSPS: New Source Performance Standards

NSR: New Source Review
NWS: National Weather Service

O2: Oxygen Ozone

OTAG: Ozone Transport Assessment Group

Pb: Lead

PCC: Program Compliance Credit

PM2.5: Particulate Matter less than 2.5 microns in size PM10: Particulate Matter less than 10 microns in size

PMT: Personal Miles Traveled

PPB: Parts per Billion PPM: Parts per Million

PSD: Prevention of Significant Deterioration
 RACT: Reasonably Available Control Technology
 RAQPC: Regional Air Quality Planning Committee
 RCAP: Regional Commute Alternatives Program

RFP: Reasonable of Further Progress

ROP: Rate of Progress

RFG: Reformulated Gasoline

RTP: Regional Transportation Plan

SA: Strategic Activity
SER: Strategic Emission Rate
SIP: State Implementation Plan

SLAMS: State or Local Air Monitoring Station

SO2: Sulfur Dioxide

SOCMI: Synthetic Organic Chemistry Manufacturing Industry

SOV: Single-Occupant Vehicle

SOx: Oxides of Sulfur

SULEV: Super Ultra Low Emission Vehicle

SUV: Sport Utility Vehicle

TAC: Technical Advisory Committee

TAFF: Texas Alternative Fuel Fleet Program

TCAA: Texas Clean Air Act

TCEQ: Texas Commission on Environmental Quality (formerly TNRCC)

TCMs: Transportation Control Measures
TCP: Transportation Control Plan

TDM: Transportation Demand Management

TEA21: Transportation Equity Act for the 21st Century (replaces ISTEA)

TERP: Texas Emission Reduction Plan

TIP: Transportation Improvement Program
TMA: Transportation Management Area

TMO: Transportation Management Organization

TNRCC: Texas Natural Resource Conservation Commission (now TCEQ)

TOG: Total Organic Gases

TPC: Transportation Policy Council

TPD: Tons per Day **TPY:** Tons per Year

TxAQS 2000: Texas 2000 Air Quality Study

TxDOT: Texas Department of Transportation (formerly Texas Highway

Department)

UAM: Urban Airshed Model

ULEV: Ultra Low Emission Vehicle

USDOT: United States Department of TransportationVMEP: Voluntary Mobile Emission Reduction Program

VMT: Vehicle Miles Traveled VOC: Volatile Organic Compound

ZEV: Zero Emission Vehicle

Executive Summary

Milestones and Background

On September 30, 2008, the Federal Highway Administration certified that the Houston-Galveston area's 2035 Metropolitan Transportation Plan (MTP) Update and the 2008-2011 Transportation Improvement Program (TIP) conformed to the requirements of the State Implementation Plan for the Houston-Galveston ozone nonattainment area. The September 30, 2008 conformity finding was established with the Revisions to the State *Implementation* Plan for Control the of Ozone Air Pollution, Houston/Galveston/Brazoria Ozone Nonattainment Area (hereafter referred to as the "RFP SIP"). This SIP did not have an Attainment Demonstration for the 1997 8-hour Ozone standard; it had a Reasonable Further Progress portion to which it was conformed using its 2008 Motor Vehicle Emission Budgets (MVEBs). The EPA found these MVEBs adequate on March 21 2008 and approved them on April 22 2009.

This conformity is necessary to fulfill the need to update the *Regional Transportation Plan* (RTP) and the *Transportation Improvement Program* (TIP). Since the last conformity, a few projects already included in the transportation plan have changed in scope and/or timing. In some cases, the projects were originally modeled incorrectly in the travel demand model analysis for the RTP. Some changes were significant enough to warrant a new conformity determination for the RTP and TIP. Following is the list of all projects that were changed on this conformity determination:

- IH 45N HOV lanes from FM 1960 to LP (loop) 336 S change milestone year; advance from 2025 to 2019.
 - FM 1960 to FM 2920 (MPO ID# 12725)
 - ➤ FM 2920 to Harris/Montgomery county line (MPO ID# 12724)
 - ➤ Montgomery county line to SH 242 (MPO ID# 12599)
 - > SH 242 to LP 336 S Add new project to database (MPO ID# 14109 & 14628)
- BF (Business Farm to Market Road) 1960 from FM 1960 west of Humble to FM 1960 east of Humble rescope from added capacity to access management treatments. Modeled under (MPO ID# 53 & 54)
- Allendale Extension: Oaks Rd. and Judy St. remove project from RTP; local sponsor has withdrawn the project (MPO ID# 13611)
- Little York between Airline and Hardy Toll Road change from 6 lanes (in 2025 and 2035) to 4 lanes (in 2019, 2025 and 2035). Cancel MPO ID#14590 (6 lanes) from database Modeled under MPO ID#4098.
- Dulles Ave from SH 6 to US 90A project incorrectly modeled as widening from 4 to 6 lanes; project will reconstruct 4 through lanes and add 2 auxiliary lanes (MPO ID# 11184). FM 2234 from FM 521 to SH 288 modeled as widening to 6 lanes (MPO ID# 12758); project is to widen from 2 to 4 lanes.

- SH 105 Cleveland Bypass modeled as widening to 6 lanes; project is to widen to 4 lanes in 2025 (MPO ID# 14633)
- SH 105 in Montgomery County modeled as 6 lanes; project should be 4 lanes; revise limits as Walden Road to Old River Road (0.870 miles) as 6 lanes in 2025 (MPO ID#7704)
- SH 146 modeling has been modified according to project description:
 - ➤ From Red Bluff to NASA 1: Widen to 8-lane with GS at major intersections and 4-lane frontage roads (MPO ID# 139)
 - From NASA 1 to Harris/Galveston County line: Widen to 6-lane arterial with 4-lane express lanes (MPO ID# 14632)
 - ➤ From Harris/Galveston County line to FM 518: Widen to 6-lane arterial with 4-lane express lanes (MPO ID#13842)
- SH 87 Galveston Ferry Landing to Bolivar Ferry Landing Toll Bridge remove from RTP (MPO ID#12435 (model), MPO ID#13866 (RTP))
- SH 242 @ IH 45 Direct Connectors project delayed due to funding shortfall remove from 2009 network (MPO ID#13513)
- FM 646 from IH 45 to FM 517 Widen from 2 to 4 lanes remove from 2009 network (MPO ID#9708)
- FM 1314 S of Gene Campbell Blvd to 2.6 MI NW of LP 494 Widen to 4 lanes remove from 2009 network (MPO ID#11558)
- FM 1314 1.0 MI S of SH 242 to S of Gene Campbell Blvd Widen to 4 lanes remove from 2009 network (MPO ID#496)
- FM 1484 FM 3083 to FM 2432 Widen to 4 lanes remove from 2009 network (MPO ID#11186)

The new TIP and RTP are scheduled for consideration and approval by the Transportation Policy Council (TPC) in August and by the Federal Highway Administration (FHWA) in September.

Conformity Requirements

The Clean Air Act Amendments of 1990 (CAAA) require transportation plans, programs, and projects in nonattainment areas, which are funded or approved by the FHWA or the Federal Transit Administration (FTA), to conform to the MVEBs established in the SIP. This ensures that transportation plans, programs, and projects do not produce new air quality violations, worsen existing violations, or delay timely attainment of the National Ambient Air Quality Standards (NAAQS). Conformity analysis requirements include:

- Use of the latest planning assumptions
- Analysis based on the latest emission estimation model available
- Interagency consultation, as well as a public involvement process, must be conducted during the analysis (found in Sections 7 and 8, respectively)

- Timely implementation of Transportation Control Measures (TCMs)
- An RTP and TIP that are consistent with the MVEBs established in the applicable SIP
- Include all regionally significant projects expected in the nonattainment area in the RTP and TIP

Regional Inventory

H-GAC conducts regional emission analyses of transportation plans to ensure that these activities are consistent with the air quality goals identified in the RFP SIP. This conformity analysis of the Houston-Galveston-Brazoria (HGB) nonattainment area accounts for emissions resulting from the nonattainment area's transportation plans, including all regionally significant projects and the effects of emission control programs.

Motor Vehicle Emission Budgets

The budgets established in the RFP SIP are as follows:

Table 1: RFP Review Motor Vehicle Emission Budgets

Reasonable Further Progress Budget (tpd)					
Year	NOx	VOC			
2008	186.13	86.77			

Source: RFP SIP, TCEQ

These MVEBs represent the maximum allowable amount of emissions that may be produced by on-road sources as a result of the implementation of the RTP and TIP. These budgets are developed based on the emission inventories and the analysis conducted for the development of the RFP SIP and include emission reduction benefits from federal and state control programs.

Conformity Tests

As specified by the Code of Federal Regulations (40 CFR §93.109[c], as amended by 62 FR 43807, Aug. 15, 1997) all ozone nonattainment areas designated moderate and above must pass a motor vehicle emissions budget test if an approved SIP budget exists. The HGB area has been designated as "Severe" for the 1997 eight-hour standard with an attainment year of 2019. As noted earlier, the budget test must be satisfied using the MVEBs established in the RFP SIP. Specifically, this test is satisfied when emissions of the ozone pollutant's precursors (VOC and NOx) for each analysis year are less than or equal to the MVEBs established in the SIP. For the test, the regional emission analysis may be performed for any years within the timeframe of the transportation plan, provided they are not more than ten years apart, the attainment year (2019) and the plan horizon year (2035). To meet this analysis requirement then, the years 2009, 2019, 2025 and 2035 were selected.

Modeling

Two modeling suites were used in this process in order to obtain total emissions. The Travel Demand Modeling at H-GAC used the EMME/2 model with a special post-mode choice speed model in order to establish the region's total vehicle miles traveled (VMT). The TTI suite of emissions software was used in conjunction with the latest version of EPA's MOBILE6 model to replicate the on-road modeling performed in the SIP and obtain the appropriate emissions factors. The data used in this conformity analysis is consistent with what was used in the SIP, except where more recent planning assumptions have been developed. Total emissions were then calculated by multiplying the VMT by the emission factors for each of the analysis years.

Conformity Analysis Results

The results of this conformity determination show that the 2035 Regional Transportation Plan and the 2008-2011 Transportation Improvement Program for the HGB Transportation Management Area meet the requirements of the SIP for the Houston-Galveston ozone nonattainment area, as submitted to EPA on May 30, 2007, and in accordance with the Clean Air Act (42 U.S.C. 7504, 7506 (c) and (d)), as amended on November 15, 1990, and the final conformity rule (40 CFR Parts 51 and 93).

Table 2: Conformity Analysis Summary

Analysis Year	VOC Emissions (tons/day)	VOC Budget (tons/day)	NOx Emissions (tons/day)	NOx Budget (tons/day)
2009	78.74	86.77	154.32	186.13
2019	46.14	86.77	50.09	186.13
2025	42.65	86.77	39.70	186.13
2035	51.03	86.77	43.05	186.13

Figure 1: VOC Emissions Summary





Figure 2: NOx Emission Summary



Background Information on Conformity

More information on what conformity is and the regulations that apply to it can be found at: http://www.fhwa.dot.gov/environment/conform.htm. This conformity determination involved a pre-analysis review discussion with the review agencies (Section 7) and a public comment period (Section 8).

1.0 Introduction

With the signing of the Clean Air Act Amendments of 1990 (CAAA) into law, the Houston-Galveston region was designated nonattainment for exceeding the National Ambient Air Quality Standard (NAAQS) for the pollutant ozone. Following the revocation of the 1-hour ozone standard, the Houston-Galveston region was labeled as "moderate" for the 8 hour ozone standard and given until the year 2009 to attain. Then due to the failure to submit an attainment SIP for 2009, the Governor requested to EPA to reclassify the region to "severe". On September 18, 2008, the EPA granted the governor's request to voluntarily reclassify the HGB ozone nonattainment area from a moderate to a severe nonattainment area for the 1997 ozone standard. The effective date of this reclassification is October 31, 2008. The EPA set April 15, 2010, as the date for the state to submit a revised SIP addressing the severe ozone nonattainment requirements. The HGB areas new attainment date for the 1997 ozone standard is as expeditiously as practicable but no later than June 15, 2019.

The CAAA requires each state to submit a state implementation plan (SIP) to the U.S. Environmental Protection Agency (EPA). The SIP is a legally binding document that defines the structure through which emissions will be reduced and the ozone standard will be attained. As the central focus of the air quality planning process, the SIP ties in transportation planning through the conformity provisions in the CAAA. These provisions verify that federal actions on transportation projects are consistent with the air quality objectives contained in the SIP. In many cases, transportation-related control measures identified in the SIP are contained and funded in the Regional Transportation Plan (RTP) and the Transportation Improvement Program (TIP).

Section 176(c)(4) of the CAAA requires the EPA to make rules regarding conformity determinations for transportation plans and programs. In response to this requirement, the EPA published its *Criteria and Procedures for Determining Conformity to State or Federal Implementation Plans of Transportation Plans, Programs, and Projects Funded Under Title 23 U.S.C. or the Federal Transit Act in the Federal Register on November 24, 1993.* This conformity rule requires metropolitan planning organizations (MPOs) and the U.S. Department of Transportation (U.S. DOT) to make conformity determinations on metropolitan transportation plans and transportation improvement programs before they are adopted, approved or accepted in air quality nonattainment areas.

1.1 MPO Organization and Role

The Houston-Galveston Area Council (H-GAC) has been designated by the State of Texas as the Metropolitan Planning Organization (MPO) charged with coordinating transportation planning for the region. H-GAC's Transportation Policy Council (TPC) is responsible for the development of the long-range, 30-year transportation plan for the

eight-county Transportation Management Area (TMA). The eight counties that form the TMA are Brazoria, Chambers, Fort Bend, Galveston, Harris, Liberty, Montgomery and Waller. The ozone nonattainment boundaries are the same as the MPO boundaries. The TPC provides regional coordination with various stakeholders including cities and counties in the eight-county area, the Texas Department of Transportation (TxDOT), transportation agencies (such as transit, toll and port authorities) and citizens of the region.

This conformity is necessary to fulfill the need to update the 2035 *Regional Transportation Plan* (RTP) and the 2008-2011 *Transportation Improvement Program* (TIP). Since there is not yet an approved attainment SIP for the 1997 8-hour ozone standard, the plans will have to conform to the MVEBs contained in the 8-hour Reasonable Further Progress SIP.

1.2 Purpose

To demonstrate conformity, as defined by the EPA's final rule, analyses of transportation plans and TIPs must address the following criteria:

- Are the RTP and TIP consistent with the most recent estimates of on-road mobile source emissions?
- Do the RTP and TIP provide for expeditious implementation of transportation control measures (TCMs) in the applicable SIP?
- Do the RTP and TIP contribute to annual emission reductions consistent with Section 182(b) and Section 187(a)(7) of the CAAA?

This criteria is met and conformity is demonstrated if both VOC and NOx emissions in each of the analysis years modeled conforms to the criteria in Section 1.3.

1.3 Conformity Criteria

The final conformity rule requires MPOs in air quality nonattainment areas to conduct conformity determinations on their transportation plans and TIPs. The rule requires that conformity analyses adhere to a number of criteria:

- The analysis process must use the most recent planning assumptions in force at the time of the conformity determination and employ the latest available and approved emissions model.
- The transportation plan and TIP must provide for the timely implementation of TCMs from the applicable SIP.
- A regional emissions analysis must be conducted for significant air quality milestone years and the RTP horizon year.

- VOCs and NOx emissions from each analysis year must be less than the MVEB established in the applicable SIP.
- Emissions from each analysis year must be less than 1990 baseline emission levels.

1.4 Document Format

The format and content of the conformity documentation was determined by the Technical Working Group (TWG). The TWG is a group of technical on-road modelers, planners, and engineers from MPOs and councils of government across the state, as well as representatives from state and federal agencies. This document includes:

- Summary of economic/demographic inputs to the travel modeling process by analysis year;
- Listing of emission model inputs by analysis year;
- Determination of regional transportation emissions;
- Estimates of emission reductions from TCMs and a demonstration of their timely implementation;
- Adjustments to estimated vehicle miles traveled based on a historic comparison to the Highway Performance Monitoring System (HPMS);
- Summaries of travel demand forecasts (person, vehicle and transit trips by mode and purpose) and summaries of vehicle miles of travel (by major functional classifications and vehicle speed) for each analysis year;
- Listings of regionally significant federal, state and local added capacity highway and transit projects by analysis year, including funding source; and
- Network link listings by analysis year.

1.5 Electronic Data Submittal

This document is available in hard copy and in electronic format. Submittal of the conformity to review agencies will be in electronic format, except to agencies that have specifically requested a printed copy. Additionally, this material is available on the H-GAC Conformity Web site:

http://www.h-gac.com/taq/airquality/conformity/2009/default.aspx

1.6 Checklist

The Documentation Subcommittee of the TWG created the checklist. The checklist is in Appendix 17. This document serves the dual function of reminding the submitting agency

to submit everything listed on the sheet, and to serve as a quick reference for review agencies.

2.0 2035 RTP & 2008-2011 TIP Conformity to the SIP

The purpose of this document is to demonstrate that the 2035 RTP and the 2008-2011 TIP conform to the MVEBs established in the RFP SIP.

2.1 Overview

The 2035 Regional Transportation Plan (RTP) considers the transportation needs of the eight-county HGB region. It is a long-range plan that identifies mobility and access goals for our region, strategies to meet these goals, and priority actions to be implemented by 2035. The area covered by this plan includes Harris, Galveston, Brazoria, Fort Bend, Montgomery, Liberty, Chambers, and Waller counties. These counties comprise the consolidated metropolitan statistical area (CMSA), a region of more than 7,000 square miles and almost 5 million residents.

2.2 Submittal Frequency

According to the 2005 Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU), which was signed into law on August 10, 2005, the RTP is required to be updated every four years. The TIP is the four-year program of transportation investments and is considered the implementation tool of the long range plan. When either the RTP or the TIP is updated, a new conformity analysis must be conducted. Additional conformity triggers include the publication of SIPs containing new MVEBs and expiration of the four-year period for which a conformity determination lasts.

2.3 Transportation Control Measures (TCMs)

The transportation control measures are reasonable available control measures that are committed to the SIP.

The 2008-2011 TIP includes and clearly identifies the reasonable available control measures committed to in the SIP for our region. The transportation activities are part of the voluntary mobile emissions reduction program and conform to the regional air quality goals. The MPO is committed to completing these projects within the required attainment timeframe. The emissions benefits for these projects and all committed CMAQ funded projects are located in Appendix H of the TIP. The project selection process for the TIP requires project sponsors to provide information pertaining to their public involvement and environmental justice process. Each sponsor is encouraged to provide documentation including meeting schedules, minutes, comments and petitions/surveys. Information regarding outreach materials and meeting locations are also identified through the selection process. Sponsors include information regarding advertising and meetings conducted in multiple languages, low-income and elderly areas, and meeting locations accessible to transit.

2.4 Regionally Significant Projects

The 2008-2011 TIP includes all regionally significant projects regardless of funding source, since the HGB region is a nonattainment area. Regionally significant projects using federal or state highway funds are located in Chapter 2 and locally funded regionally significant projects are identified in Chapter 4 of the TIP. Chapter 3 of the TIP contains all federal, state or locally funded projects that are related to transit activities. This chapter also contains and clearly identifies the projects that are expected to be transferred from FHWA programs to FTA programs.

Regionally significant roads are identified as: interstate/toll roads, other urban freeways or expressways, rural principal arterials, and urban minor arterial roads or streets. Regionally significant projects are defined as:

- 1. The project must be a non-exempt roadway project which meets the following criteria:
 - a. Proposed roads that will likely meet federal criteria for all-arterial or higher functional classification.
 - b. Upgrade to arterial or higher functional classification.
 - c. An added capacity project being constructed on new alignments as a bypass to a principal arterial/interstate.
 - d. Addition of through traffic lanes of 1 mile or more on roads that are functionally classified as an arterial or higher as defined in the travel model.
 - e. New interchanges on roads that are functionally classified as an arterial or higher, that represent new connections.
 - f. Adding or extending freeway auxiliary/weaving lanes from one interchange to a point beyond the next interchange.
- 2. As traffic conditions change in the future, the MPO's in consultation with the interagency consultation group, will consider regional significant all future roadways facilities that carry an average of 11,000 vehicles per day for a 2 lane facility and 20,000 vehicles per day for a 4 lane or greater facility between logical termini.
- 3. Any fixed guideway transit service including light rail, commuter rail, or portions of bus rapid transit that involve exclusive right-of-way (including barrier separated HOV lanes) shall be considered regionally significant.
- 4. Non-exempt projects not addressed in the above statements will be decided on a case-by-case basis through the interagency consultation process. The consultation will occur before taking the plan to TPC (either plan or TIP revision), and prior to the environmental determination.

2.5 Regionally Significant Travel Programs

The 2035 RTP proposes a collection of solutions to minimize the growth of congestion associated with our growing population. The strategies to maximize mobility include a

variety of approaches which have developed and evolved since the previous transportation plan. The 2035 RTP includes a combination of strategies, programs, and projects to improve regional mobility and quality of life for all citizens. Public Outreach comments over the years consistently articulate an urgent need for congestion reduction, improved mobility, and an increase in travel choices. The 2035 RTP employs four major strategies to aid in the goals of improving regional mobility and safety, and reducing congestion, while minimizing the associated negative air quality impacts. This RTP recommends maximizing the following strategies:

- System Capacity increasing highway and transit capacity
- Demand Management for peak-period travel
- Operations Management improving the efficiency of existing facilities
- Livable Centers coordinating land use and transportation investments

2.5.1 System Capacity

This section provides an overview of the recommended system capacity improvements contained in the 2035 RTP including roadways, transit (inside and outside of the METRO service area), and port/airport expansions.

Transit

The 2035 METRO Long Range Plan is an iterative process incorporating the 2035 METRO Solutions Plan and future mobility needs identified in regional planning efforts. The plan recommends significant expansion of the current transit system and includes a network of integrated high capacity transit facilities on major travel corridors. METRO's 2035 Long Range Plan also identifies significant service expansions beyond the METRO service area.

HOT/HOV Lanes

Begin the conversion to dual direction tolled facilities in major corridors in existing Bus/HOV Corridors.

Ports and Airports Expansion Plans:

- Continued development of a major container and cruise terminal complex called the Bayport Terminal Project, developed by the Port of Houston Authority
- The Port of Galveston expansion plans reflect increases in their cruise ship activity
- The Port of Freeport's major expansion plans include cargo handling capabilities
- The northeast side of Bush Intercontinental Airport may provide access to the proposed I-69 NAFTA Superhighway
- Expansion of passenger facilities at Hobby Airport

2.5.2 Demand Management

Travel demand management focuses on moving people, rather than moving vehicles. Its primary goal is to modify travel habits so that demand is lessened through incentive or disincentive programs. Such programs encourage increased utilization of other transportation modes, travel during non-rush hour periods, and alternate routing.

Examples of travel demand management programs include teleworking, vanpools, and congestion pricing.

2.5.3 Operations Management

Operational improvements include the continued installation and usage of Computerized Traffic Management Systems (CTMS) with video camera surveillance and incident detection and response, ramp metering and Arterial Traffic Management Systems (ATMS) that will interconnect traffic signals along specific corridors. Additional strategies are recommended related to Intelligent Transportation Systems (ITS).

Smart Streets is another operations management concept. Smart Street enhancements will help decrease vehicle delay through a range of options, such as traffic light synchronization, deployment of roundabouts, medians, constructing or extending turn bays (as needed), consolidation of duplicate driveways and partial grade separation of some traffic lanes at major intersections, as appropriate.

A viable safety evaluation and improvement program is an integral component of the 2035 RTP.

A Security-Evacuation plan is being develop in the case of hurricanes or major regional emergencies.

2.5.4 Livable Centers: Connecting transportation and land use

The 2035 RTP has shown that more significant mobility gains are possible through better coordinated land use and transportation planning. H-GAC has identified a three-pronged land use and transportation coordination strategy that calls for the: creation of bicycle and pedestrian friendly **Centers**; establishment of better **Connections** between the centers, and designs based on the **Context** of the surrounding land uses. In addition to enhancing mobility choices, this **3C's** strategy is expected to produce economic, environmental and "quality of place" benefits for the region.

2.6 Locally Funded Projects/Programs

Federal and state revenues for building and maintaining the region's transportation network are not keeping pace with demand. One method of generating additional resources is through the creation of toll facilities that provide additional sources of funding. These additional sources of revenue may provide the necessary funding for implementing regional improvements to the transportation network without necessarily requiring federal funds. The following projects may be supported with toll revenue:

- I-10 West (Katy freeway) HOT lane (under construction)
- SH 99 (Grand Parkway) Full corridor (proposed)
- Northwest corridor (new facility) New corridor (proposed)
- SH 35 New corridor (proposed)
- U.S. 290 HOT lane (proposed)
- SH 288 HOT lane (proposed)
- Hardy Toll Road extension

Westpark expansion

2.7 Exempt Projects/Programs

Exempt projects include safety, landscaping and those projects with minimal environmental impacts. Examples of such projects are:

Safety

- Hazard elimination program
- Shoulder improvements
- Pavement resurfacing and rehab
- Fencing
- Increasing sight distance
- Traffic control devices other than signalization

Mass Transit

- Purchase of support vehicles
- Construction of passenger shelters
- Purchase of office equipment
- Operating assistance to transit agencies

Other

- Projects that do not lead to construction activities
- Planning and technical studies
- Sign removal
- Landscaping
- Engineering to access social, economic or environmental impacts
- Repair of damage by natural disasters

2.8 Constraints

The EPA has designated the eight-county HGB area as nonattainment for ground-level ozone (O₃). While transportation is not this region's only source of ozone precursor pollutants, continued reductions of pollutants from on-road vehicles is an essential part of our plan to attain clean air standards. Consequently, the RTP and TIP are required to conform to emission limits set by the Texas Commission on Environmental Quality (TCEQ) and approved by the EPA.

In addition to the conformity requirements discussed above, the RTP and TIP must meet certain statutory planning requirements, as set out in 23 CFR Part 450 and 49 CFR part 613. The sections below discuss these constraints.

2.8.1 Long-Range Financial Constraint (RTP)

The fiscal constraint requirement is intended to ensure that the total estimated costs of projects included in the RTP and the estimated cost of constructing, operating, and maintaining the total (existing plus planned) transportation system over the period of the RTP does not exceed reasonably available estimated revenues. A conformity determination on fiscally constrained plans ensures that conformity findings are based on realistic plans and programs, and that TCMs and other projects which may be beneficial to air quality are funded.

The total estimated range of expenditures in the 2035 RTP is \$108.4 - \$138 billion. The 2035 RTP includes significant expansion of toll financing for limited access roadways and the use of 'surplus' toll funds for other regional transportation needs. The RTP estimates \$10 billion toll revenue through 2035 with potential for \$6 billion in revenue beyond construction, plus operations and maintenance costs for the toll facilities.

On-road mobile transportation is one of several broad categories contributing to the formation of ground-level ozone. To meet the federal air quality standard in this region, reductions are needed from all source sectors. The 2035 RTP recommends increased funding for H-GAC's mobile source emission reducing programs, such as:

- \$460 million for the Clean Vehicle Program over the life of the RTP
- \$198.8 million for the vanpool program through 2035
- \$11.6 million for FY 2007-2035 for implementation of the Commute Solution's telework initiative
- \$136.4 million for other Commute Solution programs, including: marketing and advertising of Commute Solution programs and Clean Air Action, TMO development, Best Workplaces for Commuters, and Commuter and Transit Services Pilot Programs.

2.8.2 Short-Range Financial Constraint (TIP)

The TIP was developed within the estimated allocations for the HGB region for FY 2008-2011. The fiscal constraint for the TIP ensures that those projects committed to can be implemented within the four-year timeframe. Fiscal constraint of the TIP also ensures that our region will be financially able to maintain and operate the existing transportation infrastructure.

2.8.3 Air Quality/Motor Vehicle Emissions Budgets

The MVEBs for the Reasonable Further Progress (RFP) SIP are as follows:

Reasonable Further Progress MVEBs 2008				
NOx	186.13 tpd			
VOC	86.77 tpd			

The 2008 budgets also apply to the years 2009, 2019, 2025 and 2035. The 2008 budget was calculated by TCEQ according to EPA guidance on the development of budgets under the 8-hour ozone standard, as no eight-hour Attainment Demonstration SIP has been approved for the HGB area.

3.0 Modeled Activity

This section describes the demographic modeling, as well as the travel demand modeling completed for the conformity analysis years.

3.1 Land-Use Model

Base Year (2005) Data

The three major data sources for the base year are appraisal data (from county appraisal districts), demographic data (from the U.S. Bureau of the Census), and employment data (company-level data from a proprietary Info-USA database).

Forecast Process

There are two major phases in the forecasting process. In phase I, H-GAC develops county-level control totals for population, households and employment. In phase II, H-GAC allocates these control totals to specific areas within each county.

Phase I

The development of county-level totals for population, number of households, and number of jobs for future years (from 2005 through 2035) is a multi-step process. H-GAC starts by forecasting the total population in the region (all eight counties combined) using a national population projection from the U.S. Bureau of the Census and applying to it our projection of the region's share in the total U.S. population. In the next step, H-GAC allocates the regional population forecast to the counties using the shares from the two projections (known as "0.5" and "1.0" scenarios) of the county population growth developed by the Texas State Data Center and the Office of the State Demographer. Then, H-GAC derives the forecast for the number of households in each county from the ethnic and age compositions (drawn from the scenarios) of the forecasted county populations and demographic statistical relationships obtained from the 2000 Census data. H-GAC's regional employment forecast is driven by the available future population in the working age labor force. The regional employment forecast is then allocated to the counties using projected shares in the regional employment.

Phase II

For small area allocation H-GAC uses the UrbanSim Land Use Forecasting and Simulation Model. The model breaks the region up into very small, regularly spaced squares where each square has an area of one million square feet, or approximately 23 acres. UrbanSim then analyzes land use dynamics, and determines statistical relationships between different types of land uses and various factors, such as proximity to population and employment, land values, and accessibility over the transportation network. Based on that information, the model makes predictions about the likelihood of certain type of development in certain parts of the region. The model works by "creating" housing units and job slots (non-residential square footage) and then allocating population and employment growth (defined by county control totals) into available housing and job locations.

While the elementary geographic unit of the forecast is the UrbanSim grid cell, the forecast results are available for different geographic units (Regional Analysis Zones, Transportation Analysis Zones, Census Tracts, cities, zip codes). For travel demand modeling purposes, the forecast for Travel Analysis Zones (TAZ) is derived by aggregating (summing up) results for individual UrbanSim grid cells located within TAZ.

The development of the forecast was overseen by the Forecast Advisory Committee comprised of local experts on demographic, economic, and development trends in the H-GAC region. During summer and fall of 2005, H-GAC conducted five forecast workshops, open to general public, throughout the region where the preliminary results were presented and feedback was received. Once the committee approved the draft forecast for public review and comment, the forecast results were provided to all local governments within the TMA, and were placed on H-GAC's website for review by the public. The H-GAC's Board of Directors adopted the forecast in February 2006.

Conformity Analysis Years

The H-GAC forecast includes county control totals and small TAZ-level data for every year from 2005 through 2035. The summary forecast data for the conformity years is presented in a table below.

<u>Table 3: Comparison of Forecast Data for Conformity Years</u>

		Brazoria	Chambers	Fort Bend	Galveston	Harris	Liberty	Montgomery	Waller	Region
	2009	306	34	504	289	4,016	86	429	44	5,710
Population	2019	377	41	665	345	4,660	103	578	56	6,825
(thousands)	2025	420	46	775	374	5,075	113	680	64	7,547
	2035	496	53	958	412	5,840	131	865	80	8,835
	2009	106	12	168	112	1,434	29	156	14	2,032
Households	2019	135	16	236	137	1,693	36	219	19	2,490
(thousands)	2025	153	18	275	150	1,863	40	261	22	2,782
	2035	184	21	344	169	2,173	47	336	28	3,302
	2009	100	9	153	115	2,221	23	123	14	2,758
Jobs	2019	117	10	201	135	2,561	27	162	17	3,230
(thousands)	2025	127	11	233	146	2,754	29	187	19	3,507
	2035	148	13	298	169	3,145	34	240	23	4,069

Source: H-GAC, February 2006

3.2 Travel Demand Model

3.2.1 Model Description

To address the conformity tests, analysis year networks were developed for 2009, 2019, 2025, and 2035. Results from the 2002 base year network, developed for the Base Year Emission Inventory, are used for comparison. The HGB regional travel models were used to estimate the daily travel inputs to this conformity analysis.

3.2.2 Model Validation

These models have been validated for the 2002 base year. Documentation of this validation is presented in Appendix 3. The procedures used to develop disaggregate time-of day travel and speed inputs are the same as those used in the development of the MVEBs located in the Mid-Course Review SIP for the HGB nonattainment area.

3.2.3 Network Development

The regional roadway networks used in the conformity analysis represent the system of roadways assumed to be operational in each of the five analysis years. For example, the 2009 roadway network represents current roadways, plus roadways under construction, and roadways expected to be operational by the end of FY 2009. The 2019 network includes all roadways in the 2009 roadway network plus all roadways expected to be operational by the end of FY 2019. This procedure is likewise repeated for all the other analysis years.

3.2.4 Model Adjustments

Travel Demand output is adjusted by two factors: highway performance monitoring system (HPMS) and seasonal adjustment factors. The HPMS adjustment factor was used to adjust the 2002 travel demand model (TDM) for HPMS consistency. The current TDM validation year is 2002. This factor was developed for this conformity using the 2002 TDM validation document (H-GAC, November 2006), the estimated intrazonal VMT for the 2002 TDM, and the 2002 HPMS vehicle miles of travel (VMT) reported by TxDOT.

In order to compare Base Year 2002 estimated regional VMT to HPMS estimated 2002 VMT, an estimate of total model estimated regional VMT is calculated. Model assigned regional network VMT is combined with assigned regional centroid connector VMT and an estimate of travel within each zone (intrazonal VMT). Because the reconciliation is made for estimated non-summer weekday VMT, both VMT estimates (model and HPMS) are made to represent non-summer weekday VMT. The model VMT is produced in its original form as non-summer weekday VMT, as shown. HPMS VMT represents average annual daily travel (AADT) and is adjusted to represent average non-summer weekday travel, based on an adjusted factor developed using TxDOT permanent traffic recorder data.

Model estimated average non-summer weekday travel (ANSWT)

- = (Model network VMT) + (Model Centroid Connector VMT) + (Model Intrazonal VMT)
- = (117,334,840) + (11,443,779) + (747,712)
- = 129,526,331

HPMS estimated average non-summer weekday travel (ANSWT)

- = (HPMS AADT) * (AADT to Non-Summer Weekday Travel Adjustment Factor^A)
- = (122,832,328) * (1.0558338)
- = 129,690,524

A - taken from 2002, 2009 and 2012 Emission Inventory Document, TTI, August 2005

The factor used to reconcile model estimated regional VMT to HPMS estimated regional VMT is calculated by dividing the HPMS estimated average non-summer weekday VMT as follows:

HPMS Adjustment Factor

- = (HPMS estimated ANSWT) / (Model estimated ANSWT)
- = (129,690,524) / (129,526,331)
- = 1.001267641

This HPMS factor used in the conformity analysis was not the same that was utilized in the SIP. The seasonal factor used in this analysis also differs from that used in the SIP.

The HGB regional ATR-based seasonal day-type factors adjust the travel model and estimated intrazonal VMT to VMT estimates characteristic of the day used to produce the MVEB. The factors are average episode day-type traffic count divided by the ANSWT traffic count. The seasonal factor used in this conformity is 0.97344 calculated by TTI on May 19, 2009.

3.2.5 Transit Systems

In September 1994, the Metropolitan Transit Authority (METRO) Board of Directors approved a fare increase. Prior to September 1994, there had been no transit fare increase since the previous conformity determination of the MTP. However, since summer 1997, ridership levels have risen. The analysis of marketing/survey data appears that revised fare structures and increased marketing efforts have played a role in the enhanced ridership levels.

Assumptions regarding the level of transit service for the conformity determination of the MTP are consistent with METRO's 2035 Regional Transit Plan and subsequently completed Major Investment Studies. Transit fares were assumed to remain at existing levels throughout the analysis period. Both existing and future toll facilities were evaluated assuming currently reflected toll pricing would remain at a fixed amount.

3.2.6 Roadway VMT

Base Year (2002) Inventory

Using the 2002 household and employment information for the eight-county Transportation Management Area (TMA), trip generation (i.e., production and attraction) estimates were developed for each of twelve trip purposes: home-based work (HBW), home-base-non-work-retail (HBNW-Retail), home-base-non-work-education-1 (HBNW-Ed1), home-base-non-work-school-bus (HBNW-Sch-Bus), home-base-non-work-other (HBNW-Other), home-base-non-work-airport, (HBNW-Airport), non-home-base-workbased (NHB-Workbased), non-home-base-Other (NHB-Other), external-local-auto (Ext-Loc-Auto), External-local-truck (Ext-Loc-truck), Truck trips (TR) and Taxi trips (TX). The trip production models used to produce these estimates are cross-classification

models based on household size and income, while the attraction models are based on employment. The 2002 external-local and external-through trip tables were based on 2002 external station (cordon) volumes.

Table 5 details the resulting person and vehicle trip estimates by purpose for the year 2002. The HBSCH, HBSHP and HBO trips have been summed to a home-based, non-work (HBNW) total.

<u>Table 4: Base Year (2002) Internal Trips by Purpose for the Eight-County Transportation</u>
Planning Region

Purpose	2002	% of Total
HBW Person Trips	3,097,497	19
HBNW Person Trips	7,788,474	47
NHB Person Trips	4,765,089	29
TRTX Vehicle Trips	879,624	5
Total Internal Trips	16530684	100

Source: H-GAC, 2009

Using a 2002 highway network and a set of F-factors calibrated and validated to the year 2002, person trips by purpose, as well as the truck-taxi and external-local vehicle trips, were distributed using the Disaggregate Trip Distribution Model (the Atomistic Model) of the TxDOT Trip Distribution Package (TTDP).

Table 6 details, by a general facility type structure, the 2002 network, which was used in the trip distribution, as well as the assignment phases of this scenario analysis.

Table 5: 2002 Network for the Eight-County Transportation Planning Region

Miles	Freeway/Tollway	Principal Arterial	Other Arterial	Collector	HOV Lanes ^A
Centerline	497.0	810.0	3,230.0	1,135.0	44.0
Lane	2,820.0	3,372.0	8,754.0	2,368.0	44.0

Source: H-GAC; A: excluding ramp structures, 2009

Transit mode shares were estimated based on Metro's 1995 Transit On-Board Survey. Following the estimation of transit mode share, the mezzo-level high-occupancy vehicle (HOV) carpool model of the TTDP was used to account for and estimate the level of usage of the HOV lane system by carpools and convert the person trip tables to vehicle trip tables. The HOV carpool demand on the 1995 HOV lane system was estimated based on the transit mode share estimates produced by METRO and the auto occupancy estimates from the 1984 H-GAC Regional Travel Survey (subsequently revised based on the 1990 Nationwide Personal Transportation Survey (NPTS)).

The vehicle trip tables were factored by trip purpose to represent the time periods desired for the estimation of time-of-day travel demand following the conversion of the person trip tables to vehicle trip tables. The procedure used by H-GAC to factor trip tables relies on time-of-day trip table factors by trip purpose and the trip table factoring procedures of the TTDP. The trip table factors were developed based on an analysis of the 1995 H-GAC Regional Travel Survey data. Because the Regional Travel Survey contained no data on truck/taxi and external travel, survey data from other urban areas was used to

develop trip table factors for those trip purposes.

In addition to factoring the 24-hour trips to represent the desired time period, the trip tables were converted from production-to-attraction orientation to origin-destination orientation. The factors used to perform this step were also based on the 1995 H-GAC Regional Travel survey.

<u>Time-of-Day Trip Table Factors</u>

Based on analyses of the trip table factors developed in 60 minute intervals, the daily vehicle trip tables were separated into the following time periods:

A.M. Peak: 6:01 a.m. - 9:00 a.m. Midday: 9:01 a.m. - 3:00 p.m. P.M. Peak: 3:01 p.m. - 7:00 p.m. Overnight: 7:01 p.m. - 6:00 a.m.

Following the separation of the 24-hour trip tables by purpose for each of the four time periods, the trip tables for each trip purpose were summed to develop a single time-of-day trip table (e.g., A.M. Peak trip table). Each time-of-day trip table was then assigned to the appropriate 2002 time-of-day network.

The time-of-day networks are the 2002 network with capacities reflective of the appropriate time-of-day. For example, the facilities represented in the 2002 a.m. peak network have three-hour, peak-period capacities that vary by facility type, number of lanes, and area type.

The resulting time-of-day link volume estimates were then entered into H-GAC's post-assignment speed model to develop link-level time-of-day speed estimates. The post-assignment speed model is based on procedures recommended in Highway Vehicle Speed Estimation Procedures for Use in Emissions Inventories prepared by Cambridge Systematic for the EPA in September 1991.

The speed estimation model relies primarily on the speed estimation techniques described in the Highway Capacity Manual (HCM). The HCM relationships are used to estimate the speeds for estimated volume-to-capacity ratios from zero to one. The extensions of the models for volume-to-capacity ratios exceeding one are based on the traditional Bureau of Public Roads (BPR) impedance adjustment function. The methods rely on the estimated volume-to-capacity ratio as a key measure of congestion for estimating the congested speed based on the constrained equilibrium volume of a link. Separate procedures are used for freeways and non-freeway streets.

The speed model was developed and calibrated by applying speeds to the 2002 a.m. and p.m. peak-period assignments for the HGB region, and comparing the modeled directional speeds to more than 22,000 observed directional link speeds encoded in the link data. The models were also validated to year 2002 observed directional speeds.

The centroid connectors in the HGB TMA networks represent local street facilities that provide access to higher-level roadway facilities. Local streets are generally low-volume, uncongested streets. Since there is not a one-to-one correspondence between centroid connectors and the local streets (i.e., a single centroid connector usually represents more than one local street) and since local streets generally operate without significant congestion, the speed models were not used to estimate the centroid connector speeds. The speeds for the VMT represented on centroid connectors were estimated based on the area type of the zone, which is connected to the roadway network by the centroid connector and the length of the centroid connector. The estimated speed for intrazonal VMT (travel within a zone) is developed from the average of the centroid connector speeds for the zone.

The estimated level of travel (VMT) and congestion (speed) by link serve as inputs to the emissions model.

Analysis Years (2009, 2019, 2025 and 2035)

Using the household and employment forecasts for 2009, 2019, 2025, and 2035, trip generation estimates (i.e., production and attraction) were developed for each of twelve trip purposes. The trip production models used to produce these estimates are cross-classification models based on household size and income, while the attraction models are based on employment. Trip generation estimates for external-local and extrapolating historic growth in traffic between 1995 and 2002 developed external-through vehicle trips for all scenarios. The results are shown in the table below.

<u>Table 6: Internal Trips by Purpose for the Eight-County Transportation Planning Region</u> for 2009, 2019, 2025 and 2035

Purpose	2009	% Of Total	2019	% Of Total	2025	% Of Total	2035	% Of Total
HBW Person Trips	3,705,775	18.9	4,497,731	19.0	5,023,284	19.1	5,913,730	19.2
HBNW Person Trips	9,227,890	47.0	11,053,979	46.7	12,294,175	46.7	14,379,083	46.6
NHB Person Trips	5,677,061	28.9	6,868,557	29.1	7,652,123	29.1	8,997,730	29.1
TRTX Vehicle Trip	1,031438	5.3	1,225,439	5.2	1,355,068	5.1	1,589,095	5.1
Total Trips	19,642,164	100	23,645,706	100	26,324,650	100	30,879,638	100

Source: H-GAC, June 23, 2009

As noted in Section 3.2.3, the regional roadway networks used in the conformity analysis represent the system of roadways assumed to be operational in each of the five analysis years. Table 7 summarizes the regional roadway networks for the years 2009, 2019, 2025 and 2035. Appendix 7 contains a link-level listing of the roadway modeling networks used in the analysis.

<u>Table 7: Roadway Networks for the Eight-County Transportation Planning Region for</u> 2009, 2019, 2025 and 2035

	Miles	Freeway/Tollway	Principal Arterial	Other Arterial	Collector	Managed Lanes ^A	TOTAL
2009	Centerline	684	1957	3151	1780	126	7,698
2009	Lane	4149	6170	9628	4157	150	24,254
2019	Centerline	936	2154	3213	1806	181	8,290
2019	Lane	5677	7306	10617	4606	470	28,675
2025	Centerline	967	2859	2871	1654	194	8,545
2023	Lane	6022	10707	10149	4642	538	32,058
2035	Centerline	967	3072	2684	1645	204	8,572
2033	Lane	6177	11541	9436	4637	536	32,328

Source: H-GAC, June 23 2009; A: excluding ramp structures

The estimates of person trips by trip purpose, along with network descriptions of the roadway and transit facilities and services, were then put into the regional mode choice model. This model developed forecasts of person trips by eight auto sub modes (single-occupant non-toll, single-occupant toll, two-person non-toll, two-person toll, three-person non-toll, three-person toll, four-plus-person non-toll and four-plus-person toll) and six transit sub modes (walk to local bus, walk to express bus, walk to commuter bus, walk to urban rail, drive to park and ride and drive to kiss and ride) for each of the analysis years.

Travel Model Results

The results of the travel models reflect the expected demographic trends in the region over the next couple of decades, as shown in Table 8. From 2009 to 2035, VMT is forecasted to climb more than 80 percent from about 130 million to a total of nearly to 240 million VMT per day in the region. For a summary of HPMS and seasonal factors affecting the final VMT, please refer to the Pre-Analysis Consensus Plan in Appendix 17. This document is part of the interagency consultation process.

<u>Table 8: Vehicle Miles Traveled for the Eight-County Transportation Planning Region for 2009, 2019, 2025 and 2035</u>

Analysis Year	Vehicle Miles of Travel (VMT)
2009	146,175,430.8
2019	189,233,602.2
2025	215,802,168.7
2035	260,103,499.1

Source: H-GAC, July, 2009 (VMT HPMS Adjusted)

4.0 Emission Factors/MOBILE Model

The U.S. EPA MOBILE model is at the center of this conformity analysis. This model generates emission factors (in grams/mile) for 28 vehicle categories for a wide variety of years. This conformity analysis utilized MOBILE6.2.03, which is the most recent version of this model. Emissions analysis methodologies in this conformity are consistent with procedures used to estimate the emissions budgets in the RFP SIP. The interagency consultative process was used to define any necessary changes to emission calculations due to federal or state control measures that have been promulgated since the modeling for the RFP SIP was conducted.

4.1 Overview

This conformity analysis used a directional link-based hourly methodology to develop emissions estimates. This methodology replicates the methodology used in setting the MVEB. EPA's MOBILE6.2.03 model was used to develop emissions factors by:

- Hour;
- MOBILE6 road type (or drive cycle); and
- 28 vehicle types

The speed sensitive freeway and arterial emissions factors, and the fixed-speed ramp emissions factors were used. The freeway emissions factors were applied to links with interstate, freeway, and toll roads functional classification codes; the ramp emission factors were used with links coded as ramp (for freeway, toll roads, and frontage roads); and arterial emissions factors were applied to all other links. Emission factors are later combined with the TDM output that has been adjusted using the HPMS and seasonal adjustment factors. The HGB 8-hour RFP climatic inputs to the MOBILE model were developed by TCEQ, on January 8, 2009, based on guidance from EPA for use in producing HGB RFP EIs with MOBILE6.2.03. The hourly climatic input features of MOBILE6.2.03 are applied for this effort. The hourly features include: hourly temperatures, hourly relative humidity, 24 hour average barometric pressure, and sunrise/sunset times. These inputs were used for all years and all scenarios. The basic 1990 base year EI temperature development procedure as described in the guidance document "Procedures for Emissions Inventory Preparation, Volume IV: Mobile Sources" (EPA, 1992) was used to produce the climatic inputs to MOBILE6.2.03 for the current HGB RFP EI effort. The most recent three years of weather observation data are used. TCEQ developed these values based on climate data from the 10 highest ozone exceedance days from the period 2006 through 2008.

ATR-based hourly travel fractions were applied to allocate the episode day type VMT by hour-of-day. Hourly, directional, average operational speeds were modeled by link. Vehicle classification data were used to estimate time-of-day VMT mixes for apportioning fleetwide link VMT for the three road type groups (freeway, arterial and ramp) to the 28 EPA vehicle types. Link-level emissions by vehicle type were calculated by hour.

4.2 MOBILE Input Parameters

A full list of MOBILE6 input parameters can be found in Appendix 8. These parameters correspond to the parameters used in the on-road modeling for the attainment demonstration SIP, except where more recent planning assumptions have replaced the earlier data. New data includes updated registration distributions, diesel fractions, VMT mix, and new seasonal adjustment factors. It should also be noted that there is no Inspection and Maintenance (I/M) program in the rural counties. This modification is reflected in the MOBILE setups. Appendix 8 presents all data inputs, including activity data, local meteorological data, state control programs, federal control programs, and vehicle fleet characteristics.

4.3 Emission Factor Adjustments

Emission factor post-processing was required to properly model the vehicle Anti-Tampering Program (ATP) and I/M Program, the Texas Low-Emissions Diesel Fuel Program (TxLED), and the implementation of new federal emission standards for motorcycles. The county-level, episode-day-specific emissions factors were organized into tables which were input to the emissions calculations (Section 6).

5.0 Mobile Source Emission Reduction Strategies

This section covers a variety of on-road emission control programs.

5.1 TCMs

A Transportation Control Measure (TCM) is a measure specifically committed to in a SIP for the purpose of reducing emissions from transportation sources. TCMs are further defined in 40 CFR §93.101, as amended by 62 FR 43780, 43803. The CAA required that TCMs be included in SIPs for regions designated as serious and above ozone nonattainment areas. The TCMs committed to in the previous SIPs are listed in Appendix 13.

5.1.1 Timely Implementation of TCMs

The transportation conformity rule includes specific criteria for determining if TCMs that are included in a SIP are being implemented in a timely manner. The intent of these provisions is to ensure that TCMs which are eligible for federal funding receive priority and that the SIP schedules and commitments are enforced. Appendix 13 details the current status of regional TCMs. The TCM Appendix has emission estimates associated with each project. These were developed using the mobile source emission reduction strategies (MoSERS¹) methodology in combination with MOBILE6 emission factors. While emissions were calculated for each project, these credits were not applied in this conformity analysis. Please refer to Section 6.

5.1.2 Project "Slippage"

For TCM projects that have slipped behind schedule, regions are required to identify the obstacle that caused the slippage and to document how the issue will be resolved. These requirements are detailed in 40 CFR §93.113(c)(1-3), as amended by 62 FR 43780, 43809-10. No project slippages have occurred for the committed TCMs.

5.2 VMEPs

The Voluntary Mobile Emissions Reduction Program (VMEP) includes a number of onroad and off-road emission reduction programs that go beyond currently mandated programs. While each individual effort is voluntary, it is mandatory that the overall program achieve the emission reductions specified in the Attainment SIP. Since this conformity is not using the MVEB from an Attainment SIP, this section is just added as a courtesy to FHWA. This region has committed to a range of VMEPs which are detailed in Appendix 4. This appendix also provides an updated estimate of emissions benefits

¹ For more information on the Mobile Source Emission Reduction Strategy (MoSER) calculation methodologies please see the handbook at http://moser.tamu.edu/.

resulting from these measures. Credit for the on-road measures will not applied to the final emission numbers in this conformity.

5.3 *CMAQ*

The Congestion Mitigation and Air Quality Improvement Program (CMAQ) is a categorical funding program created with ISTEA and continued under TEA-21 and SAFETEA-LU. This program directs funding to projects that contribute to meeting NAAQS. CMAQ funds generally may not be used for projects that result in the construction of new capacity available to single-occupant vehicles. For a listing of TIP-funded CMAQ projects, please refer to Chapter 2, and for their emission benefits please refer to Appendix H of the 2008-2011 TIP.

5.4 TERP

The Texas Emissions Reduction Plan (TERP), established by the legislature in 2001, is a comprehensive set of incentive programs aimed at improving air quality in Texas. The Texas Commission on Environmental Quality (TCEQ) administers TERP grants and other financial TERP incentives. The RFP SIP did not use this program to calculate the MVEB for 2008, therefore this conformity is not going to use it as a credit. Further information on TERP can be found on the TCEQ website, http://www.tceq.state.tx.us/implementation/air/terp/

5.5 Summary

The programs mentioned above typically cannot be modeled in the usual regional emissions modeling process. As a result, off-model credit must be calculated and applied. These calculations are detailed in their respective appendices. These on-road programs illustrate the commitment this region has made to improving air quality.

6.0 Determination of Regional Transportation Emissions

Estimates of on-road mobile source emissions are based on recent model runs of H-GAC's travel demand forecasting models (Section 3) and the EPA's MOBILE6.2.03 emission factor model (Section 4), post-process adjustments (this section), and off-model credits (Section 5). Regional emissions analyses for conformity must contain the following:

- 1. All federal projects and all regionally significant non-federal projects;
- 2. All regionally-significant projects, regardless of funding source, are required to be included in the model; and,
- 3. VMT from all other projects (including TCMs) that are not required to be explicitly modeled must be estimated based on reasonable professional practice (see Section 5).

Conformity analyses must estimate emissions for certain future years called horizon years. These horizon years have very specific requirements:

- 1. Horizon years may be no more than 10 years apart;
- 2. The first horizon year may be no more than 10 years from the base year used to validate the transportation demand planning model;
- 3. If the attainment year is in the time span of the transportation plan, the attainment year must be a horizon year; and
- 4. The last horizon year must be the last year of the transportation plan's forecast period.
- 5. If the budget year is in the time span of the transportation plan, the budget year must be a horizon year.

Based on these requirements, the years 2009, 2019, 2025 and 2035 were selected for analysis in this conformity. Emissions calculations in a conformity must follow the calculations used in the SIP. This section summarizes the final steps in the emissions estimation process.

6.1 Procedure

The Texas Transportation Institute developed a suite of programs (hereafter referred to as the "TTI suite" or the "suite") that facilitates the calculation of regional emissions. The suite works in conjunction with the MOBILE6 model, discussed in Section 4, to generate emission factors, and applies these factors to the Travel Demand Modeling results in Section 3.

Figure 3 is a basic flowchart of how the TTI suite of programs is applied. The hexagons in this flow chart indicate where data inputs are required. The "Start" in the upper left hand corner symbolizes the point where the air quality modeler has been given the travel demand modeling output. Following the down arrow, MOBILE6 input factors are developed as described in Section 4. At this point POLFAC62 is utilized to run MOBILE6.2.03 to produce emission factors for:


- 1. all control programs,
- 2. all counties,
- 3. all roadways,
- 4. all vehicle types, and
- 5. all hours of the day.

The resulting emission factor files are then fed into the RATADJ62 program, which takes the multiple sets of emission factors for each county and combines them into a single set of emission factors. At this point, the emission factors are ready to combine with the Travel Demand Model output.

Figure 3: TTI Suite

Computational Process Flow

Travel Demand Model Network Link-Based Hourly MOBILE6
Emissions Estimates with Texas Mobile Source Emissions Software



Source: TTI, 2004

To the right of the "Start" in the flow chart is the TRANSVMT model. This model takes the Travel Demand Model output and puts it in the correct format. The TRANSVMT module operates in TransCAD®. These outputs are ready to be combined with the emission factors already generated. The IMPSUM program multiplies the appropriate emission factors with the appropriate VMT for each hour of the day. The hourly IMPSUM outputs are summed by SUMALL and reported in a tab delimited format (please see the "Emissions" folder in the electronic documentation). The post-process adjustments are made to the SUMALL output. Appendix 6 provides a more thorough explanation of the TTI Suite of programs.

6.2 Calculated Link-Based Emissions

The link-based emissions, as they are summarized by the SUMALL step, appear in Table 9. These emissions have further post-processing steps before they are final.

Years	NOx (tpd)	VOC (tpd)
2009	161.75	78.76
2019	51.75	46.31
2025	40.78	42.88
2035	44.11	51.32

Table 9: Non-Adjusted Link-Based Emissions

6.3 Post-Process Adjustments

Referring to the flow chart again, post-process adjustments take place in the last square before the end labeled "emissions adjustments." The SUMALL output is run through the TTI ADJ programs to adjust for diesel idling, temperature/humidity, motorcycle, and the TxLED and motorcycle measures. Detailed descriptions of these measures can be found in Appendix 5. The adjustments applied in this step follow the same methodology that was developed for the SIP. These adjustments are outlined in Table 10. Please note that the "Idling" calculation is not an emission reduction: as in the SIP, this calculation redistributes 3 percent of the on-road heavy-duty vehicle emissions to idling vehicles at truck stops. Since no idling reduction measures are in place, no credit can be taken. This calculation was included in the conformity to ensure that the calculation process for conformity was as similar to the calculation in the SIP as possible.

<u>Table 10: Post-Processing Emissions</u>

Post Process Steps	2009	(tpd)	2019	(tpd)	2025	(tpd)	2035	(tpd)
	NOx	VOC	NOx	VOC	NOx	VOC	NOx	VOC
Unadjusted	161.75	78.76	51.75	46.31	40.78	42.88	44.11	51.32
Idling	0	0	0	0	0	0	0	0
Temp/Humidity	-2.88	0	-0.64	0	-0.38	0	-0.37	0
Motorcycle/TxLED	-4.55	-0.02	-1.02	-0.17	-0.70	-0.23	-0.69	-0.29
VMEP								
TERP								
Final Emissions	154.32	78.74	50.09	46.14	39.70	42.65	43.05	51.03

6.4 Final Emission Analysis Results

Mobile source emissions estimated for the 2035 RTP and the 2008-2011 TIP are consistent with the most recent projections of population, employment, travel and congestion available. The 2035 RTP demonstrates timely attainment of TCM targets established in the SIP and provides for expeditious implementation of additional measures designed to reduce congestion and vehicular travel demand. VOC and NOx emission estimates from all the analysis years, shown in Table 11, are lower than those estimated for the 1990 base year. Additionally, final VOC and NOx emissions for the years 2009, 2019, 2025 and 2035 are lower than the VOC and NOx budgets established by the RFP SIP. The 2035 RTP and the 2008–2011 TIP, therefore, pass all conformity tests required under the EPA's Final Conformity Rule. The transportation improvements in the 2035 RTP Update and the 2008 -2011 TIP conform to both the SIP and the Clean Air Act, as amended.

Table 11: Final Emission Results

Analysis Year	VOC Emissions (tpd)	VOC Budget (tpd)	NOx Emissions (tpd)	NOx Budget (tpd)
1990 Baseline	321.700		391.100	
2008		86.77		186.13
2009	78.74	86.77	154.32	186.13
2019	46.14	86.77	50.09	186.13
2025	42.65	86.77	39.70	186.13
2035	51.03	86.77	43.05	186.13

7.0 Interagency Consultation

Interagency review and comment on the conformity finding was conducted in accordance with the consultative process identified in the Conformity SIP. Local, state, and federal transportation and air quality agencies affected by this conformity analysis were consulted on the scope, methodologies and products of the conformity finding. A conformity steering committee (Conformity Consultation Committee) composed of representatives of each of the following agencies was consulted regularly during the conformity process:

- Houston-Galveston Area Council (H-GAC)
- Metropolitan Transit Authority of Harris County (METRO)
- City of Houston (CoH)
- Harris County
- Texas Department of Transportation (TxDOT)
- Texas Commission on Environmental Quality (TCEQ)
- Texas Transportation Institute (TTI)
- Federal Highway Administration (FHWA)
- Federal Transit Administration (FTA)
- U.S. Environmental Protection Agency (EPA)

The purpose of this group was to ensure that the modeling methodology utilized in this conformity analysis was consistent with the on-road modeling utilized in the SIP and that the most recent planning assumptions were used. A comprehensive list of the CCC meeting agenda and decisions can be found in Appendix 15.

8.0 Public Participation

Public participation is an important part of the conformity process. A 30-day public comment period is required by Federal regulation. All documentation for this conformity will be distributed to the consultation committee in the form of CDs and also posted on H-GAC's website in July 2009 (http://www.h-gac.com/taq/airquality/conformity/2009/default.aspx). This website will be further utilized to post draft conformity material as it is developed by H-GAC and reviewed by the CCC. The actual public comment period will continue for more than the required 30 days.

The official public comment period begins on July 22, 2009 and concludes August 22, 2009. A public meeting will be held on August 13, 2009 at H-GAC (3555 Timmons Lane, Houston, Texas). Comments received are responded to in Appendix 16. The minutes from the public hearing can also be found in the same appendix.